



Pro-Loc™ Tape Fittings



Easy to Spot. Tough to Beat.

Easy to install Pro-Loc tape fittings offer a comprehensive range of configurations including couplings, layflat take-offs and valve options. Engineered for use with quality 16mm and 22mm tape, Pro-Loc fittings are designed to last for the life of the irrigation system.

Features and Benefits:












Pro-Loc tape fittings deliver the quality you expect from Toro for reliable performance, season after season.







- Tight Seal - Coarse thread ensures a tight seal, even in dirty conditions.
- Easy to Install - Long double barb for positive installation.
- Easy to Grip - Ergonomically designed nut provides a secure connection every time.
- Easy to See - Bright blue nut makes tape fittings easy to find, remove and reuse.
- Low Profile - Compact design doesn't interfere with retrieving the tape.
- UV Resistant - Tough anti-UV stabiliser to suit Australian conditions.

Designed for reliable, proven results when used with Aqua-Traxx™, Pro-Loc fittings are also suitable for use with other leading tape brands. For optimal performance, use Pro-Loc in conjunction with PC Aqua-Traxx - Australia's only pressure compensating drip tape available exclusively from Toro Australia.



Pro-Loc™ Tape Fittings

Couplings		
	FTC500	16mm Tape Coupling
	FTC700	22mm Tape Coupling
Barb Adaptors		
	FTA5-250B	16mm Tape x 250 Series Barb Adaptor
	FTA5-400B	16mm Tape x 400 Series Barb Adaptor
	FTA5-700B	16mm Tape x 700 Series Barb Adaptor
	FTA7-700B	16mm Tape x 700 Series Barb Adaptor
	FTA5-425G	16mm Tape x 425 Series Barb Adaptor with Intergral Gasket*
	FTA5-425GR	16mm Tape x 425 Series Barb Adaptor with Rubber Grommet*
	FTA7-425GR	22mm Tape x 425 Series Barb Adaptor with Rubber Grommet*
Adaptors		
	FTA5-75MPT	16mm Tape x 20mm MPT Male Adaptor
	FTA5-75FHS	16mm Tape x 20mm Female Hose Swivel Adaptor
Flush Valves		
	FFVFPT-L	Automatic Flush Valve x 20mm Female Low Flow - White
	FFVFPT-H	Automatic Flush Valve x 20mm Female High Flow - Red
	FTA5-FVL	16mm Tape x Low Pressure Flush Valve
	FTA7-FVL	22mm Tape x Low Pressure Flush Valve
Layflat Takeoff Fittings		
	FTA5-LF	16mm Tape x Layflat Takeoff - Single Grip**
	FTA7-LF	22mm Tape x Layflat Takeoff - Single Grip**
Adaptors		
	FTA5-500HB	16mm Tape x 500 Series Hose Barb Adaptor
	FTA5-700HB	16mm Tape x 700 Series Hose Barb Adaptor
	FTA7-700HB	22mm Tape x 700 Series Hose Barb Adaptor
Tees		
	FTT500	16mm Tape Tee
	FTT700	22mm Tape Tee

Barbed Tees		
	FTT5-500HB	16mm Tape Tee x 500 Series Hose Barb
	FTT5-700HB	16mm Tape Tee x 700 Series Hose Barb
Shutoff Valves		
	FTV500	16mm Tape Shutoff Valve
	FTV700	22mm Tape Shutoff Valve
Barbed Shutoff Valve with Locking Nut		
	FTV5-420BN	16mm Tape x 420 Series Barb with Locking Nut Shutoff Valve
	FTV5-500HN	22mm Tape x 500 Series Hose Barb with Locking Nut Shutoff Valve
Barbed Shutoff Valves		
	FTV5-500HB	16mm Tape x 500 Series Hose Barb Shutoff Valve
	FTV7-500HB	22mm Tape x 500 Series Hose Barb Shutoff Valve
Layflat Takeoff Shutoff Valves		
	FTV5-LF	16mm Tape x Layflat Takeoff Shutoff Valve
	FTV7-LF	22mm Tape x Layflat Takeoff Shutoff Valve
T-Handle Hex Tool		
	LF-INST	T-Handle Hex Tool for Layflat Installation

*15mm or 0.59" drill size

** requires a 16mm layflat puch

Pro-Loc™ Fittings Selection Guide			
Nominal Size	Series Number	Inside Diameter Tolerance	Wall Thickness Tolerance
		Millimeters	Millimeters
16mm & 17mm	500	13.2 - 15.0	0.50 - 1.40
18mm	600	15.2 - 16.5	0.75 - 1.40
20mm	700	17.2 - 18.5	0.80 - 1.40
22mm	800	20.0 - 21.5	1.00 - 1.50

For more information, please phone
1300 130 898 or visit www.toro.com.au

 Toro Australia Pty Ltd