



# REVOLUTION BACKPACK AND LEAF BLOWER CANNON

#### Model 66200

- Comfortable, sturdy backpack with integrated handle, LED battery diagnostics and capacity to carry two batteries
- Interchangeable arm cannon or power tether
- Powerful blower, 730 CFM (1,240 m³/h) at 160 MPH (257 km/h)\*\*
- Variable speed trigger with turbo boost and cruise control
- Included storage strap for compact footprint
- Powered by any 60V MAX\* Flex-Force battery
- Tool only, batteries and chargers sold separately
- 2-year commercial use warranty



# **REVOLUTION LEAF BLOWER CANNON**

## Model 66200T (Bare Tool) - Backpack required

- 730 CFM (1,240 m³/h) at 160 MPH (257 km/h)\*\* for massive air volume that makes easy work of every pile
- Variable speed trigger with turbo boost button and cruise control lets you effortlessly match power to the situation
- Brushless motor optimises performance, runtime, efficiency, and tool life
- LED battery fuel gauge always shows you where your power stands
- Powered by any 60V MAX\* Flex-Force battery
- Tool only, batteries and chargers sold separately
- 2-year commercial use warranty

	Revolution Blower Cannon
Boost Mode†	37 min
High Run Time†	80 min
Peak Run Time†	330 min
Weight (Bare Tool)	17.4 lbs (7.9 kg)
Air Volume**	730 CFM (1,240 m <sup>3</sup> /h)
Air Speed**	160 MPH (257 km/h)



## **REVOLUTION STRING TRIMMER**

## Model 66210T (Bare Tool)

- Rugged solid shaft design
- 16" (40.6 cm) cutting width with 0.095" (2.4 mm) line
- Bump-feed/easy-load head with increased line capacity and durability
- Rear-mounted high efficiency brushless motor
- Variable 2-speed operation
- Powered by any 60V MAX\* Flex-Force battery
- Tool only, batteries and chargers sold separately
- 2-year commercial use warranty

	Revolution String Trimmer
High Run Time^	160 min
Peak Run Time <sup>^</sup>	240 min
Weight (Bare Tool)	10.1 lbs (4.6 kg)
RPM <sup>^</sup>	6,400/5,300



## Model 66220T (Bare Tool)

- 26" (66 cm) bar with 1.2" (3 cm) cut capacity
- Dual-sided cutting blades
- 180° rotating handle for vertical or horizontal cutting
- Top side blade guard for operator protection and plant gathering
- Variable 2-speed with 4,100/3,200 spm<sup>^</sup>
- Blade reverse mode for unsticking jams
- Class-leading runtime: up to 600 minutes^
- Powered by any 60V MAX\* Flex-Force battery
- Tool only, batteries and chargers sold separately
- 2-year commercial use warranty

	Revolution Hedge Trimmer
Peak Run Time^	600 min
Weight (Bare Tool)	9.2 lbs (4.2 kg)
Strokes per Minute	4,100/3,200

Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features.

Based on 2 x 10 Ah batteries, at low speed in controlled laboratory testing of product. \*Based on 10 Ah battery, at low speed in controlled laboratory testing of product. \*See your local Toro dealer for details on all warranties.

<sup>\*</sup>Battery manufacturer rating = 60V maximum & 54V typical usage. Actual voltage varies with load.

<sup>\*\*</sup>Up to 730 CFM Max and 160 MPH Max on turbo boost. Performance claims based on controlled laboratory testing.



# REVOLUTION BACKPACK

#### Model 66205T

- Removable battery system with capacity for up to two batteries
- Interchangeable arm cannon or power tether
- Comfortable and sturdy backpack system for all-day operation
- Integrated carrying handle
- Onboard LED battery diagnostics
- Powered by any 60V MAX\* Flex-Force battery
- Tool only, batteries and chargers sold separately
- 2-year commercial use warranty



# **REVOLUTION POWERLINK TETHER**

## Model 66005

- Keeps your backpack power source connected to your handheld tools.
- Removes battery weight from tools: faster work and less fatique.
- Doubles handheld tool battery capacity so you always have power at hand.



# **60V MAX\* 10 AH BATTERY**

#### Model 68810

- 33% more capacity than current largest 60V battery
- 10 Ah battery is interchangeable in all Revolution 60V tools
- Easily removable and can be quickly swapped to refuel tools
- Integrated carrying handle
- Increased over-mould for ruggedisation and drop resistance
- Weighs 8.2 lbs (3.7 kg)



## **60V MAX\* 6-POD CHARGER**

## Model 66560

- 12 AMP rapid charger
- 6-battery capacity
- Can charge any combination of 60V MAX\* Flex-Force batteries
- 2 charge modes
- Sequential rapid mode can charge a single 10 Ah battery in 50 minutes (7.5 Ah in 38 minutes)
- Standard equal mode slowly brings all batteries up to full charge collectively
- 2-year commercial use warranty

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs, and standard equipment without notice and without incurring obligation.

Many of the products you will find in certified Toro dealers' stores come with a warranty or guarantee from The Toro Company. In addition, our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. Full details of your consumer rights may be found at www.consumerlaw.gov.au

\*Battery manufacturer rating = 60V maximum and 54V typical usage. Actual voltage varies with load.
-See your local Toro dealer for details on all warranties.



# toro.com.au

Worldwide Headquarters The Toro Company 8111 Lyndale Ave. So. Bloomington, MN 55420 U.S.A. Phone: (1) 952 888 8801 Fax: (1) 952 887 8258

©2023 The Toro Company. All Rights Reserved. IND-C0257 11-2023













facebook.com/toroaus twitter.com/toroaus instagram.com/toroaus pinterest.com.au/toroaus au.linkedin.com/showcase/toroaustralia youtube.com/toroaustralia

