

Application

Pots, planter boxes, balcony, patio and residential landscape irrigation systems.

A pressure compensating dripper with turbulent flow path, sealed to maintain pre-set discharge rates and uniformity.

Features

- Registered design
- Pressure compensated flow rate, with turbulent flow path, self-flushing action and insect baffle to minimise blockages
- Three colour coded flow rates available: 2 Lph, 4 Lph and 8 Lph.
- Ergonomically designed for easy finger/thumb installation
- Inlet barb has built-in filter
- Outlet suitable for attaching 4mm micro tube.



Performance

Pressure (kPa)	Discharge Lph		
	2 Lph	4 Lph	8 Lph
	Red base	Black base	Green base
50	2.0	3.4	5.9
100	2.3	4.1	7.8
150	2.3	4.4	8.1
200	2.3	4.6	8.3
250	2.3	4.6	8.4
300	2.3	4.6	8.3
350	2.2	4.5	8.1

Specifications

Dimensions Assembled	BARB	
Height	25 mm	
Width	28 mm	
Depth	15 mm	
Weight (Approx)	1.1 g	
Base/Connection Type: Inlet	Barb 4mm	
Base/Connection Type: Outlet	Spout 4mm	
UV Stabilised Material	Base	Polypropylene
	Cap	Polypropylene
	Diaphragm	Silicone

Pinch Drip™ PC
Barb 4mm



Ordering Information

Code	Description
10130705	2 Lph Pinch Drip™ PC, 4mm Barb
10130715	4 Lph Pinch Drip™ PC, 4mm Barb
10130725	8 Lph Pinch Drip™ PC, 4mm Barb