

Application

Pots, planter boxes, balcony, patio and residential landscape irrigation systems. A pressure compensating, fixed flow drip emitter. Gentle flow action with uniform coverage for all emitters on same supply tube.

Features

- Patented design
- Pressure compensated flow rate
- Diameter of throw maintained by pressure compensating device over a wide range of inlet pressures.
- 8 fingers of water
- Take apart for easy inspection and cleaning.
- Coloured cap for easy identification.
- UV stabilised materials for long life.



Performance

Nominal Flow	Pressure (kPa)	Flow (Lph)	Diameter (m)
24 Lph	100	24	0.3
	150	29	0.3
	200	33	0.4
	250	36	0.4
	300	38	0.4

Specifications

Dimensions Assembled		BARB	SPIKE
Height		25 mm	135 mm
Width		20 mm	16 mm
Depth		15 mm	26 mm
Weight (Approx)		1.7 g	5.4 g
Base/Connection Type: Inlet		Barb 4mm	Barb 4mm
UV Stabilised Material	Base	Polypropylene	Polypropylene
	Cap	Polypropylene	Polypropylene
	Diaphragm	Silicone	Silicone

Ordering Information

Code	Description
10131685	Shrubbler® PC, 24 Lph, 4mm Barb
10131695	Shrubbler® PC 24 Lph, on spike, 4mm Barb



Shrubbler® 360° PC
Barb 4mm



Shrubbler® 360° PC
Spike 4mm