



16mm Drip-In PC with Rootguard - Recommended Maximum Run Length (m)

| Inlet Pressure (kPa) | Spacing (m) | | | | | | | | | | | | | | | | | | | | | | | |
|----------------------|-------------|-----|-----|-----|-----|-----|-----|-----|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| | 0.3 | | 0.4 | | 0.5 | | 0.6 | | 0.75 | | 0.9 | | 1.0 | | 1.5 | | | | | | | | | |
| | Length (m) | | | | | | | | | | | | | | | | | | | | | | | |
| 150 | 58 | 48 | 36 | 76 | 63 | 47 | 92 | 77 | 58 | 108 | 90 | 68 | 130 | 109 | 82 | 152 | 126 | 96 | 166 | 138 | 104 | 230 | 190 | 144 |
| 200 | 74 | 61 | 46 | 95 | 80 | 60 | 117 | 97 | 73 | 137 | 113 | 86 | 165 | 138 | 104 | 193 | 160 | 121 | 211 | 175 | 132 | 292 | 242 | 184 |
| 250 | 85 | 70 | 53 | 110 | 91 | 69 | 134 | 111 | 84 | 157 | 131 | 98 | 190 | 158 | 119 | 222 | 184 | 139 | 242 | 201 | 152 | 335 | 278 | 211 |
| 300 | 93 | 77 | 58 | 121 | 100 | 76 | 148 | 123 | 93 | 173 | 144 | 109 | 210 | 174 | 132 | 245 | 203 | 154 | 266 | 222 | 167 | 370 | 308 | 232 |
| 350 | 100 | 83 | 63 | 130 | 108 | 82 | 159 | 132 | 100 | 187 | 156 | 117 | 226 | 188 | 142 | 264 | 220 | 166 | 288 | 239 | 181 | 400 | 332 | 251 |
| 400 | 107 | 89 | 67 | 139 | 115 | 87 | 169 | 141 | 106 | 199 | 165 | 125 | 241 | 200 | 151 | 281 | 233 | 177 | 307 | 255 | 193 | 425 | 354 | 267 |
| Nom. Flow L/h | 2.0 | 2.4 | 4.0 | 2.0 | 2.4 | 4.0 | 2.0 | 2.4 | 4.0 | 2.0 | 2.4 | 4.0 | 2.0 | 2.4 | 4.0 | 2.0 | 2.4 | 4.0 | 2.0 | 2.4 | 4.0 | 2.0 | 2.4 | 4.0 |

Based on minimum pressure of 100 kPa. All run lengths calculated on flat ground.