



20mm Drip-In PC with Rootguard - Recommended Maximum Run Length (m)

Inlet Pressure (kPa)	Spacing (m)																							
	0.3			0.4			0.5			0.6			0.75			0.9			1.0			1.5		
150	105	87	63	135	112	80	162	135	97	188	156	112	224	186	134	258	215	154	279	232	167	378	315	225
200	133	111	80	170	142	102	205	171	122	238	198	142	284	236	170	327	272	196	355	295	212	479	400	288
250	153	127	91	195	163	117	235	196	141	273	227	164	326	272	195	376	313	225	408	339	244	552	460	331
300	168	140	100	215	180	129	259	216	155	301	251	180	360	300	215	415	346	249	449	375	270	609	509	366
350	181	151	109	232	194	139	279	234	167	325	271	194	387	324	233	447	373	268	485	405	291	657	549	394
400	193	161	115	247	206	148	297	248	178	345	289	207	412	345	248	475	398	286	516	432	310	699	586	420
Nom. Flow Lph	2.0	2.4	4.0	2.0	2.4	4.0	2.0	2.4	4.0	2.0	2.4	4.0	2.0	2.4	4.0	2.0	2.4	4.0	2.0	2.4	4.0	2.0	2.4	4.0

Based on minimum pressure of 100kPa. All run lengths calculated on flat ground.