

25mm Aqua-Traxx® Premium Drip Tube Recommended Run Length (m) Chart for varying Ground Slopes								
Code	Emitter	EU	Downhill			Flat	Uphill	
	Spacing	%	3%	2%	1%	0%	1%	2%
Medium Flow 0.76 Lph @ 55 kPa								
EA8xx1234-yyy	30cm	95	10	14	28	237	27	14
		90	54	83	527	434	121	62
		85	111	186	681	545	189	101
EA8xx2417-yyy	60cm	95	10	15	29	374	28	15
		90	54	82	172	680	124	62
		85	108	165	986	855	199	101
Standard Flow 1.02 Lph @ 55 kPa								
EA8xx0867-yyy	20cm	95	9	14	29	151	26	13
		90	55	92	355	276	113	62
		85	129	420	442	346	168	99
EA8xx1245-yyy	30cm	95	10	14	29	195	27	13
		90	55	84	454	359	118	62
		85	115	511	572	451	182	100
EA8xx2422-yyy	60cm	95	10	15	28	330	28	15
		90	54	97	182	563	124	63
		85	109	170	855	708	197	101

Run lengths apply to single laterals only with 55 kPa inlet pressure. Derate if multiple laterals are connected to a header submain.

Product Code Definition
For example EAXxx0867
X = Tape Diameter
9=9/8" (29 mm),
8=8/8" (25 mm)
xx = thickness in mil
(04=4 mil, 12=12 mil, etc.)
08 = 8" spacing
67 = 0.67 gpm per 100 feet
(mil = 1/1000th inch)