

29mm Aqua-Traxx® Recommended Run Length (m) Chart for varying Ground Slopes								
Code	Emitter	EU	Downhill			Flat	Uphill	
	Spacing	%	3%	2%	1%	0%	1%	2%
Medium Flow 0.76 Lph @ 55 kPa								
EA9xx1234-yyy	30cm	95	10	14	28	292	27	13
		90	54	83	188	531	123	61
		85	109	172	814	667	195	103
EA9xx2417-yyy	60cm	95	10	15	28	457	28	15
		90	54	82	167	833	125	63
		85	107	163	388	1044	206	102
Standard Flow 1.02 Lph @ 55 kPa								
EA9xx0867-yyy	20cm	95	9	15	28	156	27	13
		90	55	86	430	338	118	62
		85	117	489	540	424	179	100
EA9xx1245-yyy	30cm	95	9	15	27	242	27	12
		90	54	83	529	440	122	61
		85	111	186	690	553	190	102
EA9xx2422-yyy	60cm	95	10	15	28	372	28	15
		90	54	81	168	688	124	63
		85	108	166	994	866	200	102

Run lengths apply to single laterals only with 55 kPa inlet pressure. Derate if multiple laterals are connected to a header submain.

Product Code Definition
For example EAXxx0867

X = Tape Diameter
9=9/8" (29 mm),
8=8/8" (25 mm)

xx = thickness in mil
(04=4 mil, 12=12 mil, etc.)

08 = 8" spacing

67 = 0.67 gpm per 100 feet
(mil = 1/1000th inch)