

## Specifications

- Flow rate: 0.2-17 Lpm
- Operating pressure for optimum nozzle performance: 200 kPa
- Recommended operating pressure range: 140-350 kPa
- Maximum operating pressure: 520 kPa

Nozzle Series	Apex at 200 kPa				
	Maximum Height of Spray				
	27°	23°	12°	5°	0°
4.6m (15')	1.4m				
3.7m (12')		1.1m			
3m (10')			0.7m		
2.4m (8')				0.66m	
1.5m (5')					0.46m

570 Series Nozzle screens*		
White	Red	Red and Metal
4.6m (15') Series	2.4m (8') Series	1.5m (5') Series
3.7m (12') Series	1.2m x 9.1m (4'x30') SST	0.6m x1.8m (2'x6') SST
3m (10') Series	1.2m x 5.5m (4'x18') SST	10° Stream Spray Series
1.2m x 9.1m (4'x30') CST Stream Bubblers		35° Stream Spray Series Flood Bubbler Series
Flat-Spray (Non-MPR)		Flat-Spray, Low Volume (Non-MPR)
1.2m x 9.1m (4'x30') EST		
2.7m x 5.5m (9'x18') SST		

\* Indicates screen provided with nozzle. Refer to current Parts Breakout Book for more information.