



# Antelco® CFd® Downspray

## The C-Frame Downspray

is a 360° spray jet that distributes water evenly across the wetted surface area. Stake assembly options provide savings in labour and installation time.

## Application

Nurseries, tree lots, pot plants, home and landscaped gardens.

## Features

- 45° downspray reduces the effect of wind.
- Gentle spray minimises damage to delicate plant foliage.
- Galvanised wire stake assembly incorporates a hole punch for easy installation.
- 3 colour coded frames to identify flow rates.
- Quick insertion thread with leak-proof design.
- UV stabilised for long life.



### CFd® Downspray (patent pending)

Colour	Orifice Size	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Black	0.8 mm	10119005	100	90	14.4
Brown	0.9 mm	10119025	100	90	14.4
Blue	1.0 mm	10119015	100	90	14.4

### CFd® Downspray Galvanised Wire Stake Assembly with Shut-Off Clip

Colour	Tube Length	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Black	914 mm	10143705	25	12	9.6
Brown	914 mm	10143725	25	12	9.6
Blue	914 mm	10143715	25	12	9.6

### Specifications

Dimensions Assembled		CFd® Downspray	CFd® Downspray Wire Stake Assembly
Height		34mm	950mm
Width		25mm	25mm
Depth		8mm	15mm
Weight (approx)		1.4g	27.8g
UV Stabilised Materials	Frame Stake Adaptor Off-Take Tube Barb Adaptor Stake	acetal	acetal polypropylene polyethylene acetal galvanised steel
Base/Connection Type: Inlet		Quick Thread with Sealing Barb 4mm	Barb 4mm

Performance		360°	
Colour and Orifice Size	Pressure (kPa)	Flow (Lph)	Diameter (m)
Black 0.8 mm	50	15	0.6
	100	22	0.6
	150	27	0.5
Brown 0.9 mm	50	20	0.6
	100	28	0.5
	150	34	0.5
Blue 1.0 mm	50	22	0.6
	100	33	0.5
	150	42	0.5